

TrailerFlap™



FLEETAERO®

Driving Your Fleet Forward

TrailerFlap™

DESIGN & SPECIFICATIONS

MATERIAL:	INDUSTRIAL GRADE INJECTION MOLDED NYLON
CHEMICAL RESISTANCE:	NOT AFFECTED BY DIESEL FUEL, MOTOR OIL, COOLANT, SALT, ACETONE, DETERGENT, OR WINDOW CLEANER
FREEZING TEST:	-25°F FOR 30 DAYS
MOUNTING:	STANDARD MOUNTING, TRIMS EASILY
THICKNESS:	.3125"
WEIGHT:	50 OZ.

TrailerFlap's chevron design reduces spray by directing the air flow and water passing through the flap towards the road surface, making it the most efficient mudflap on the market. Instead of creating substantial drag, like other mudflaps, the advanced vented design of TrailerFlap actually helps **reduce fuel consumption by 1%, typically saving 100 gallons of diesel fuel per year.**

Injection molded from an industrial grade nylon, TrailerFlap is built to withstand extreme conditions. They are unbelievably tough and highly resistant to flap "pinch," which means additional savings because you spend less on repairs or replacement costs.



2-YEAR WARRANTY

FleetAero Trailerflap is now available with AeroGuard 2-year warranty. For more information, please visit Fleetaero.com/Aeroguard.

FLEETAERO®

2465 S. 19th Ave. | Bldg. F
Phoenix, AZ 85009

For more information, quote, technical help, or parts, contact us at:

Sales | Jason.O@FleetAero.com

Support | info@FleetAero.com

(844) 462-5233

fleetaero.com