

FUEL SAVINGS:

7.15% IN SAE J1321 TEST





APPROVAL:	CARB, EPA GHG2, SMARTWAY
LENGTH:	16-22' (DEPENDING ON CONFIGURATION)
HEIGHT:	32"
WEIGHT:	147-223 LBS. (DEPENDING ON CONFIGURATION)
LOWER SKIRT:	THERMOPLASTIC VULCANITE (TPV). SLIDES INTO CLIPS ON THE PANEL (FLEET) OR RIVETS INTO PANEL (HD)
STRUT:	STEEL WITH DUAL COIL SPRINGS

TrailerBlade™ side skirts have proven **fuel savings of 7.15%** at highway speeds in strict accordance with EPA testing guidelines. Not only did TrailerBlade™ pass the SmartWay® certification requirement for an Advanced Side Skirt, but it also conclusively exceeded the certification requirement.

TrailerBlade™ side skirts are made entirely from the same durable materials used on the outside of your tractor-trailer. That's why they last longer than other side skirts in the market. In addition, the slide-in rubber skirt saves installation and repair time.

TrailerBlade™ Struts

Our patented Mounting Strut is made of high-strength steel that pivots and articulates. This four-way adjustment prevents damage and ensures a perfect installation on every trailer. The slim profile resists snow, ice, and mud buildup. And the triple-coated galvanizing protects from the effects of corrosion.

Installation

With its modular design, TrailerBlade™ installs faster than any side skirt on the market. No special tools are required. TrailerBlade™ products are all designed to be installed in less than one man hour.



10-YEAR LIMITED WARRANTY

FleetAero® side skirts are now available with FleetAero® warranty. For more information, please visit Fleetaero.com/warranty



TRAILERBLADE™ DOORS

For your convenience, we give you the option of installing TrailerBlade™ doors designed to fit any TrailerBlade™ skirt. The push button mechanism gives you easy access to spare tire, battery compartments, storage boxes, or tire chains. They're easy to install and are available in 36″ and 48″ widths for up to 6 doors per trailer.



For more information, quote, technical help, or parts, contact us at: info@FleetAero.com

(844) 462-5233